



Version No: 1

Issue date:30/APR/2024

Revision date: Not Applicable

Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878)

SECTION 1. Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier	
Product name	DHX Lysis
Synonyms	Not Available
Other means of identification	Not Available
1.2. Relevant identified uses of the substance or mixture and uses advised against	
Relevant identified uses	Laboratory use.
Uses advised against	Not Applicable
1.3. Details of the manufacturer or supplier of the safety data sheet	
Registered company name	CleanNA
Address	Coenecoop 75, 2741 PH, Waddinxveen, The Netherlands
Telephone	+31 (0) 182 22 33 50
Fax	+31 (0) 182 22 33 98
Website	www.cleanna.com
Email	info@cleanna.com
1.4. Emergency telephone number	
Emergency telephone numbers	112 (European emergency number)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture	
Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	H302 – Acute Toxicity (Oral) – Category 4 H314 – Skin Corrosion/Irritation – Category 1A H318 – Serious Eye Damage/Eye Irritation – Category 1 H412 – Hazardous to the Aquatic Environment Long-Term Hazard – Category 3
2.2. Label elements	
Hazard pictogram(s)	Two diamond-shaped hazard pictograms with red borders. The first shows two test tubes pouring liquid onto a hand and a surface, representing corrosion. The second shows a large black exclamation mark, representing a general hazard.
Signal word	Danger
Hazard statement(s)	
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H412	Harmful to aquatic life with ling lasting effects
Supplementary statement(s)	
EUH302	Contact with acids liberates very toxic gas

Precautionary statement(s) Prevention

P260	Do not breathe mist / vapours / spray
P264	Wash all exposed external body areas thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves & clothing, eye & face protection

Precautionary statement(s) Response

P310	Immediately call a POISON CENTER / doctor / physician / first aider
P363	Wash contaminated clothing before reuse
P301 + P312	IF SWALLOWED; call a POISON CENTER / doctor / physician / first aider
P304 + P340	IF INHALED: remove person to fresh air and keep comfortable for breathing
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting
P303 + P361 + P353	IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water or shower
P305 + P351 + P338	IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

Precautionary statement(s) Storage

P405	Store locked up
-------------	-----------------

Precautionary statement(s) Disposal

P501	Dispose of contents / container to authorized hazardous or special waste collection point in accordance with any local regulation
-------------	---

2.3. Other hazards

Cumulative effects may result following exposure *
May produce discomfort of the respiratory system *
May possibly be harmful to the foetus / embryo *

REACH – Art. 57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS issue date.

SECTION 3. Composition / information on ingredients**3.1 Substances**

See 'Composition on ingredients' in Section 3.2

3.2 Mixtures

1. CAS No 2. EC No 3. Index No 4. REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
1. 593-84-0 2. 209-812-1 3. 615-004-00-3 4. Not Available	50 - 100	guanidine thiocyanate	Acute Toxicity (Oral, Dermal, Inhalation) – Category 4 Hazardous to the Aquatic Environment Long-Term Hazard – Category 3 H302, H312, H332, H412	Not Available	Not Available
1. Not Available 2. Not Available 3. Not Available 4. Not Available	0.1 - 1	Anionic detergent	Serious Eye damage/Eye irritation – Category 2 Hazardous to the Aquatic Environment Acute Hazard – Category 1 H319, H400	Not Available	Not Available
Legend: 2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties					

SECTION 4. First aid measures**4.1. Description of first aid measures**

Eye Contact	If this product comes in contact with the eyes: <ul style="list-style-type: none">- Immediately hold eyelids apart and flush the eye continuously with running water- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye moving the eyelids by occasionally lifting the upper and lower lids- Continue flushing until advised to stop by the POISONS INFORMATION CENTER / doctor or for at least 15 minutes- Transport to hospital or doctor without delay- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel
Skin Contact	If skin or hair contact occurs: <ul style="list-style-type: none">- Immediately flush body and clothes with large amounts of water, using safety shower if available- Quickly remove all contaminated clothing including footwear- Wash skin and hair with running water. Continue flushing with water until advised to stop by POISONS INFORMATION CENTER- Transport to hospital or doctor
Inhalation	<ul style="list-style-type: none">- If fumes or combustion products are inhaled remove from contaminated area.- Lay patient down. Keep warm and rested.- Protheses such as false teeth which may block airway, should be removed where possible prior to initiating first aid procedures- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.- Transport to hospital or doctor

Ingestion	<ul style="list-style-type: none"> - For advice contact a POISONS INFORMATION CENTER or doctor at once - Urgent hospital treatment is likely to be needed - IF SWALLOWED DO NOT induce vomiting - If vomiting occurs: lie patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration - Observe patient carefully - Never give liquid to person showing signs of being sleepy or with reduced awareness i.e. becoming unconscious - Give water to rinse out mouth then provide liquid slowly and as much as casualty can comfortably drink - Transport to hospital or doctor without delay
-----------	--

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

For thiocyanate poisonings haemodialysis is recommended as the treatment of choice. Phenobarbital protects poisoned animals against death.

Thiocyanate ion is slowly excreted in the urine and is not decomposed to any appreciable degree to cyanide.

[GOSSELIN, SMITH & HODGE: Clinical Toxicology of Commercial products – 5th Ed]

SECTION 5. Firefighting measures

5.1 Extinguishing media

- Foam
- Dry chemical powder
- BCF (where regulations permit)
- Carbon dioxide
- water spray or fog (large fires only)

5.2 Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc, as ignition may result.
----------------------	---

5.3. Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> - Alert Fire Brigade and tell them location and nature of hazard - Wear breathing apparatus plus full body protective clothing - Prevent, by any means available, spillage from entering drains or water courses - Use water delivered as a fine spray to control fire and cool adjacent area - Avoid spraying water onto liquid pools - DO NOT approach container suspected to be hot - Cool fire exposed containers with water spray from a protected location - If safe to do so, remove containers from path of fire
Fire/Explosion Hazard	<ul style="list-style-type: none"> - Combustible - Slight fire hazard when exposed to heat or flame - Heating may cause expansion or decomposition leading to violent rupture of containers - On combustion may emit toxic fumes or carbon monoxide (CO) - May emit acrid smoke - Mists containing combustible materials may be explosive <p>Combustion products include:</p> <ul style="list-style-type: none"> - Carbon dioxide (CO₂) - Hydrogen chloride - Phosgene - Nitrogen oxides (NO_x) - Sulfur oxides (SO_x) - Other pyrolysis products typical of burning organic material <p>May emit poisonous fumes May emit corrosive fumes</p>

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

See section 8

6.2 Environmental precautions

See section 12

6.3 Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> - Remove all ignition sources. - Clean up all spills immediately - Avoid breathing vapours and contact with skin and eyes - Control personal contact with the substance by using protective equipment - Contain and absorb spill with sand, earth, inert material or vermiculite - Wipe up. - Place in a suitable, labelled container for waste disposal.
Major Spills	<ul style="list-style-type: none"> - DO NOT touch the spill material <p>Moderate hazard</p> <ul style="list-style-type: none"> - Clear area of personnel and move upwind. - Alert Fire Brigade and tell them location and nature of hazard - Wear breathing apparatus plus protective gloves - Prevent, by any means available, spillage from entering drains or water course - No smoking, naked lights or ignition sources - Increase ventilation - Stop leak if safe to do so - Contain spill with sand, earth of vermiculite

- | | |
|--|--|
| | <ul style="list-style-type: none">- Collect recoverable product into labelled containers for recycling- Collect solid residues and seal in labelled drums for disposal- Wash area and prevent runoff into drains- If contamination of drains or waterways occurs, advise emergency services |
|--|--|

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Safe handling	<ul style="list-style-type: none">- Avoid all personal contact including inhalation- Wear protective clothing when risk of exposure occurs- Use in a well-ventilated area- Prevent concentration in hollows and sumps- DO NOT enter confined spaces until atmosphere has been checked- Avoid contact with incompatible materials- When handling DO NOT eat, drink or smoke- Keep containers securely sealed when not in use- Avoid physical damage to containers- Always wash hands with soap and water after handling- Work clothes should be laundered separately.- Use good occupational work practice- Observe manufacturer's storage and handling recommendations contained within this SDS- Atmosphere should be regularly against established exposure standards to ensure working conditions are maintained- DO NOT allow clothing wet with material to stay in contact with skin
Fire and explosion protection	See section 5
Other information	<ul style="list-style-type: none">- Keep in original containers- Keep container securely sealed- No smoking, naked lights or ignition sources- Store in a cool, dry, well-ventilated area- Store away from incompatible materials and foodstuff containers- Protect containers against physical damage and check regularly for leaks- Observe manufacturer's storage and handling recommendations contained within this SDS

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none">- Metal can or drum- Packaging as recommended by manufacturer- Check all containers are clearly labelled and free from leaks
Storage incompatibility	<ul style="list-style-type: none">- Avoid strong acids, acid chlorides, acid hydrides and chloroformates- Metal cyanides are readily oxidised and those of some heavy metals show thermal instability- Metal cyanide and cyanates are often endothermic. Several members of this family of compounds contain heavy metals tend to explosive instability and most are capable of violent oxidation under certain circumstances- Fusion of mixtures of metal cyanides with metal chlorates, perchlorates, nitrites or nitrites cause violent explosion- Magnesium reacts with incandescence on heating with several metal cyanides. Release of cyanogen by thermal decomposition may cause vigorous reaction with magnesium- Addition of one solid component (even in residual amounts) to another molten component is extremely dangerous [BRETherick L: Handbook of Reactive Chemical Hazards]- Nitriles may polymerise in the presence of metals and some metal compounds- Mixing nitriles with strong oxidising acids can lead to extremely violent reactions- Nitriles are generally incompatible with other oxidising agents such as peroxides and epoxides- The combination of bases and nitriles can produce hydrogen cyanide. Nitriles are hydrolysed exothermally in both aqueous acid and base to give carboxylic acids (or salts of carboxylic acids)- Nitriles can react vigorously with reducing agents- The covalent cyano group is endothermic and many organic nitriles are reactive under certain conditions. N-cyano derivatives are reactive or unstable- The majority of endothermic compounds are thermodynamically unstable and may decompose explosively under various circumstances of initiation- Many but not all endothermic compounds have been involved in decompositions, reactions and explosions and, in general, compounds with significantly positive values of standard heats of formation, may be considered suspect on stability grounds [BRETherick L.: Handbook of Reactive Chemicals hazards]- Avoid reaction with oxidising agents
Hazard categories in accordance with Regulation (EC) No 1272/2008	Not available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not available

7.3. Specific end use(s)

See section 1.2

SECTION 8. Exposure controls / personal protection

8.1. Control parameters

Ingredient	DNELs			PNECs	
	Exposure	Pattern	Worker	Compartment	
Guanidine thiocyanate	Dermal	0.31 mg/kg bw /day	(Systemic, Chronic)	42.4 mcg/L	(Water (Fresh))
	Inhalation	1.092 mg/m³	(Systemic, Chronic)	4.24 mcg/L	(Water – Intermittent release)
	Inhalation	3.28 mg/m³	(Systemic, Acute)	424 mcg/L	(Water (Marine))
	Dermal	0.155 mg/kg mw/day	(Systemic, Chronic) *	165 mcg/kg sediment dw	(Sediment (Fresh Water))
	Inhalation	0.27 mg/m³	(Systemic, Chronic) *	16.5 mcg/kg sediment dw	(Sediment (Marine))
	Oral	0.155 mg/kg bw/day	(Systemic, Chronic) *	8.03 mcg/kg soil dw	(Soil)
				20 mg/L	(STP)

* Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Guanidine thiocyanate	0.98 mg/m³	11 mg/m³	65 mg/m³

Ingredient	Original IDLH	Revised IDLH
Guanidine thiocyanate	Not Available	Not Available

8.2. Exposure controls

8.2.1 Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of contaminant	Air Speed
Solvent, vapours, degreasing etc. evaporating from tank (in still air)	0.25 – 0.5 m/s (50 – 100 f/min)
Aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5 – 1 m/s (100 – 200 f/min)
Direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher debts, gas discharge (active generation into zone of rapid air motion)	1 – 2.5 m/s (200 – 500 f/min)
Grinding, abrasive blasting, tumbling, high speed generated dusts (released at high velocity into zone of very high rapid air motion)	2.5 – 10 m/s (500 – 200 f/min)

Within each range the appropriate value depends to:

Lower end of range	Upper end of range
1: Room air currents minimal of favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production	3: High Production, heavy use
4: Large hood or large air mass in motion	4: Small hood – local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

8.2.2. Personal protection



Eye and face protection	<ul style="list-style-type: none"> - Chemical goggles whenever there is a danger of the material coming in contact with the eyes. Goggles must be properly fitted.. - Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories. Spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing or if the material can be under pressure - Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes. These afford face protection. - Alternatively a gas mask may replace splash goggles and face shields - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. <p>[CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</p>
Skin protection	<p>See Hand protection below</p> <ul style="list-style-type: none"> - Elbow length PVC gloves - When handling corrosive liquids wear trousers or overalls outside of boots to avoid spills entering boots <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity
Hand / feet protection	<p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>
Body protection	<p>See Other protection below</p>
Other protection	<ul style="list-style-type: none"> - Overalls - PVC apron - Barrier cream - Skin cleansing cream - Eye wash unit

Respiratory protection

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AB-AUS / Class1 P2	-
up to 50	1000	-	AB-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AB-2 P2
up to 100	10000	-	AB-3 P2
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

8.2.3. Environmental exposure controls

See section 12

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10. Stability and reactivity

10.1.Reactivity	See section 7.2
10.2. Chemical stability	<ul style="list-style-type: none"> - Unstable in presence of incompatible materials - Product is considered stable - Hazardous polymerisation will not occur
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Inhaled	<p>Hydrogen chloride (HCl) vapour or fumes present a hazard from a single acute exposure. Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes.</p> <p>Inhalation of HCl may cause choking, coughing, burning sensation and may cause ulceration of the nose, throat and larynx. Liquid on the lungs followed by generalised lung damage may follow.</p> <p>Breathing of HCl vapour may aggravate asthma and inflammatory or fibrotic pulmonary disease.</p> <p>High concentrations cause necrosis of the tracheal and bronchial epithelium, pulmonary oedema, atelectasis and emphysema and damage to the pulmonary blood vessels and liver.</p> <p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p>
Ingestion	<p>Accidental ingestion of the material may be harmful. Animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion.</p> <p>A number of materials such as cyanamide, calcium cyanamide, cyanates, isocyanates, isonitrile, thiocyanates, ferricyanide and ferrocyanide and cyanoacetates do not exhibit the same toxic effects as cyanides and nitriles.</p> <p>Probable lethal dose of thiocyanate (rhodanate) in man is between 15 and 30 gm (ingested at one time). Several acute fatalities are recorded with death coming in 10 to 48 hours.</p>
Skin Contact	<p>The material can produce severe chemical burns following direct contact with the skin.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material.</p> <p>Entry into the blood-stream through, for example, cuts, abrasions or lesions may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that an external damage is suitably protected.</p> <p>Skin contact with the material may be harmful. Systemic effects may result following absorption.</p>
Eye	<p>This material can produce severe chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.</p> <p>If applied to the eyes this material causes severe eye damage.</p>
Chronic	<p>Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation with cough and frequent attacks of bronchial pneumonia may ensue.</p> <p>Chronic minor exposure to hydrogen chloride (HCl) vapour or fume may cause discolouration or erosion of teeth, bleeding of the nose and gums, and ulceration of the mucous membranes of the nose. Workers exposed to hydrochloric acid suffered from stomach inflammation and a number of cases of chronic bronchitis (airway inflammation) have also been reported. Repeated or prolonged exposure to dilute solutions of hydrogen chloride may cause skin inflammation.</p>

DHX Lysis	TOXICITY		IRRITATION
	Not Available		Not Available
Guanidine thiocyanate	TOXICITY		IRRITATION
	Dermal (rabbit) LD50	> 2000 mg/kg ¹	Skin: adverse effect observed (corrosive) ¹
	Inhalation (Rat) LC50	> 0.853 mg/24h ¹	
	Oral (Rat) LD50	474.6 mg/kg ¹	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

DHX Lysis	<p>Goitrogenic: Goitrogens are substances that suppress the function of the thyroid gland by interfering with iodine uptake which can, as a result, cause an enlargement of the thyroid (a goitre)</p> <p>Goitrogens include:</p> <ul style="list-style-type: none"> - Vitexin, a flavonoid which inhibits thyroid peroxidase, contributing to goitre - Thiocyanate and perchlorate which decrease iodide uptake by competitive inhibition and consequently increase release of TSH from the pituitary gland - Lithium which inhibits thyroid hormone release - Certain foods such as soy and millet (containing vitexins) and vegetables in the genus Brassica (which includes broccoli, Brussels sprouts, cabbage, cauliflower and horseradish) - Caffeine (found in coffee, tea, cola and chocolate) which acts on thyroid function as a suppressant <p>Thiocyanate is known to be an important part of the biosynthesis of hypothiocyanite by a lactoperoxidase. Thus the complete absence of thiocyanate or reduced thiocyanate in the human body (e.g. cystic fibrosis) is damaging to the human host defense system.</p> <p>Thiocyanate (SCN⁻) is a complex anion which is a potent inhibitor of iodide transport (the thyroid sodium-iodide symporter). Iodine is an essential component of thyroxine. Since thiocyanates will decrease iodide transport into the thyroid follicular cell, they will decrease the amount of thyroxine produced by the thyroid gland. As such, foodstuffs containing thiocyanate are best avoided by iodide deficient hypothyroid patients.</p> <p>Thiocyanate is the detoxification product of cyanide and can easily be measured in body fluids. Consumption of naturally occurring goitrogens, certain environmental toxins and cigarette smoke can significantly increase SCN⁻ concentrations to levels potentially capable of affecting the thyroid gland.</p> <p>Goiter endemics were reported to develop when the critical urinary iodine/SCN⁻ ratio decreases below 3 microgram iodine per mg SCN⁻. Iodine supplementation completely reverses the goitrogenic influence of SCN⁻.</p> <p>SCN⁻ is also generated from cigarette smoking as a detoxifying product of cyanide. During the past two decades many reports dealt with the possible effects of cigarette smoking on thyroid hormone synthesis, thyroid gland size and thyroid auto-immunity including infiltrative ophthalmopathy of Graves's disease.</p> <p>Thiocyanates are derived from the hydrolysis of glucosinolates – sulfur-containing compounds found in cruciferous vegetables. Brassica species such as cabbage, broccoli, cauliflower, rutabaga, mustard, Brussels sprouts, and turnip contain glucosinolates (previously called thioglucosides) which are hydrolyzed to form isothiocyanates, nitriles and thiocyanates.</p>
-----------	---

Guanidine thiocyanate	The material may be irritating to the eye with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
	Asthma-like symptoms may continue for month or even years after exposure to the materials ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual wit sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.
	Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on metacholine challenge testing and the lack of minimal lymphocytic inflammation without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand , industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterised by difficulty breathing, cough and mucus production.
	The material may produce respiratory tract irritation and result in damage to the lung including reduced long function. He material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

11.2. Information on other hazards

1. Endocrine Disruption Properties

Not Available

2. Other Information

See Section 11.1

SECTION 12. Ecological information

12.1 Toxicity

	Endpoint	Test duration (hr)	Species	Value	Source
DHX Lysis	Not available	Not available	Not available	Not available	Not available
	Endpoint	Test duration (hr)	Species	Value	Source
Guanidine thiocyanate	NOEC(ECx)	504	Crustacea	1.25 mg/l	2
	EC50	72	Algae or other aquatic plants	130 mg/l	2
	LC50	96	Fish	~ 89.1 mg/l	2
	EC50	48	Crustacea	42.4 mg/L	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organism, may cause long-term adverse effects in the aquatic environment.
DO NOT allow the product to come in contact with surface waters or to intertidal areas below the main high water mark.
DO NOT contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
DO NOT discharge into sewer of waterways

For thiocyanates:

Terrestrial Fate:

- Soil:
- At near ambient temperatures (approx.. 30 C) it appears that sorption and volatilization are not significant processes for thiocyanate in soil with thiocyanate losses due primarily to microbial degradation
 - Thiocyanate is not persistent in soil
 - Thiocyanate may undergo both aerobic and anaerobic microbial degradation. However the degradation pathway has not been defined.
 - Saturated soils treated with thiocyanate were found to emit carbonyl sulfide (COS).
 - Microbial degradation is the primary mechanism for thiocyanate disappearance at or below 30 C, with carbonyl sulfide as a possible hydrolysis product.
 - Loss of thiocyanate at higher temperatures (50-60 C) did not appear to result from microbial degradation

Aquatic Fate:

- Biodegradation is a significant transformation process for thiocyanates in natural waters.
- Thiocyanate is toxic to micro-organisms at high concentrations. However acclimated cultures have increased tolerance to this compound.
- At concentrations up to 1.42 g/L thiocyanate is completely degraded within 4 days to ammonia and sulfate on (SO4-2) by an acclimatized co-culture of two bacteria (Acenetobacter johnsonii and Pseudomonas diminuta).

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No data available	No data available

12.3. Bio accumulative potential

Ingredient	Bioaccumulation
	No data available

12.4. Mobility in soil

Ingredient	Mobility
	No data available

12.5. Results of PBT and vPvB assessment

	P	B	T
Relevant available data	Not Available	Not Available	Not Available
PBT	✗	✗	✗
vPvB	✗	✗	✗
PBT Criteria fulfilled?	No		
vPvB	No		

12.6. Endocrine Disruption Properties

Not Available

12.7. Other adverse effects

Not Available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none">- Containers may still present a chemical hazard/danger when empty- Return to supplier for reuse/recycling, if possible <p>Otherwise:</p> <ul style="list-style-type: none">- If container cannot be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers to prevent reuse and bury at an authorized landfill- Where possible retain label warnings and SDS and observe all notices pertaining to the product. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none">- Reduction- Reuse- Recycling- Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none">- DO NOT allow wash water from cleaning or process equipment to enter drains.- It may be necessary to collect all wash water for treatment before disposal.- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.- Where in doubt contact the responsible authority.- Recycle wherever possible or consult manufacturer for recycling options.- Consult State Land Waste Authority for disposal.- Bury or incinerate residue at an approved site- Recycle containers if possible or dispose in an authorised landfill
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
------------------	----

Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	Class	Not Applicable
	Sub risk	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Hazard identification (Kemler)	Not Applicable
	Classification code	Not Applicable
	Hazard Label	Not Applicable
	Special provisions	Not Applicable
	Limited quantity	Not Applicable
	Tunnel Restriction Code	Not Applicable

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	ICAO/IATA Class	Not Applicable
	ICAO / IATA Sub risk	Not Applicable
	ERG Code	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	Special provisions	Not Applicable
	Cargo Only Packing Instructions	Not Applicable
	Cargo Only Maximum Qty / Pack	Not Applicable
	Passenger and Cargo Packing Instructions	Not Applicable
	Passenger and Cargo Maximum Qty / Pack	Not Applicable
	Passenger and Cargo Limited Quantity Packing Instructions	Not Applicable
	Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	IMDG Class	Not Applicable
	IMDG Sub risk	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number	Not Applicable
	Special provisions	Not Applicable
	Limited Quantities	Not Applicable

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	Not applicable	Not Applicable
14.4. Packing group	Not applicable	
14.5. Environmental hazard	Not applicable	
14.6 Special precautions for user	Classification code	Not Applicable
	Special provisions	Not Applicable
	Limited quantity	Not Applicable
	Equipment required	Not Applicable
	Fire cones number	Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.8. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Guanidine thiocyanate	Not Available
Anionic detergent	Not Available

14.9. Transport in bulk in accordance with the ICG Code

Product name	Ship Type
Guanidine thiocyanate	Not Available
Anionic detergent	Not Available

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

guanidine thiocyanate is found on the following regulatory lists

Europe EC Inventory

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category	Not Available
-----------------	---------------

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
Guanidine thiocyanatee	593-84-0	615-004-00-3	Not Available

Harmonization (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Acute Tox. 4; Acute Tox. 4; Acute Tox. 4; Aquatic Chronic 3;	GHS07; Wng	H302; H312; H332, H412
2	Acute Tox. 4; Skin Corr. 1B. Eye Dam 1; Aquatic Chronic 3 ; Acute Tox. 3; Acute Tox. 3; Aquatic Acute 3; STOT SE 3	GHS05; Dgr; GHS06, GHS08	H301; H312; H314; H318; H331; H335; H402; H412

Harmonization Code 1 = The most prevalent classification. Harmonization Code 2 = The most severe classification.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (guanidine thiocyanate, Anionic detergent)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (guanidine thiocyanate)
Korea - KECI	No (guanidine thiocyanate)
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (guanidine thiocyanate)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16. Other information

Full text Risk and Hazard codes

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled

Version Summary

Version	Date of Update	Sections Updated
1	30/APR/2024	Initial version

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered. For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
AIIC	Australian Inventory of Industrial Chemicals
BCF:	Bio Concentration Factors
BEI	Biological Exposure Index
DSL	Domestic Substances List
EINECS	European Inventory of Existing Commercial chemical Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and New Chemical Substances Inventory
ES	Exposure Standard
FBEPH	Russian Register of Potentially Hazardous Chemical and Biological Substances
IARC	International Agency for Research on Cancer
IECSC	Inventory of Existing Chemical Substance in China
IDLH	Immediately Dangerous to Life or Health Concentrations
INSQ	Inventario Nacional de Sustancias Químicas
KECI:	Korea Existing Chemicals Inventory
LOAEL	Lowest Observed Adverse Effect Level
LOD	Limit Of Detection
NCI	National Chemical Inventory
NDSL	Non-Domestic Substances List
NLP	No-Longer Polymers
NOAEL	No Observed Adverse Effect Level
NZIoC:	New Zealand Inventory of Chemicals
OSF	Odour Safety Factor
OTV	Odour Threshold Value
PC	Permissible Concentration
PC-STEL	Permissible Concentration Short Term Exposure Limit
PICCS	Philippine Inventory of Chemicals and Chemical Substances
STEL	Short Term Exposure Limit
TCSI	Taiwan Chemical Substance Inventory
TEEL	Temporary Emergency Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average