

Version No: 1

Issue date: 30/APR/2024 Safety Data Sheet (Conforms to Annex II of REACH (1907/2006) - Regulation 2020/878) Revision date: Not Applicable

SECTION 1. Identification of the substance / mixture and of the company / undertaking

1.1. Product Identifier

Product name	TR Wash
Synonyms	Not Available
Other means of identification	Not Available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Laboratory use.
Uses advised against	Not Applicable

1.3. Details of the manufacturer or supplier of the safety data sheet

Registered company name	CleanNA
Address	Coenecoop 75, 2741 PH, Waddinxveen, The Netherlands
Telephone	+31 (0) 182 22 33 50
Fax	+31 (0) 182 22 33 98
Website	www.cleanna.com
Email	info@cleanna.com

1.4. Emergency telephone number

Emergency telephone numbers

112 (European emergency number)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	H302 - Acute Toxicity (Oral) - Category 4 H312 - Acute Toxicity - Category 4 H314 - Skin Corrosion – Category 1C H318 - Serious Eye damage/Eye irritation - Category 1 H332 – Acute Toxicity – category 4 H412 - Hazardous to the Aquatic Environment Long-Term Hazard – Category 3
---	--

2.2. Label elements

Hazard pictogram(s)	
Signal word	Danger
Hazard statement(s) H302 + H312 + H332	Harmful if swallowed.
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H412	Harmful to aquatic life with long lasting effects
Supplementary statement(s)	

EUH032 Contact with acids liberates very toxic gas

Precautionary statement(s) Prevention

recationally statement(s) revention		
P260	Do not breathe dust	
P264	Wash all exposed external body areas thoroughly after handling.	
P270 Do not eat, drink or smoke when using this product.		
P273	Avoid release to the environment	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
recautionary statement(s) Res	sponse	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P304 + P340 + P310	IF INHALED: remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTRE / doctor / physician / first aider	
P303 + P361 + P353 IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water.		
P301 + P312	Call a POISON CENTER/doctor/physician/first aider if you feel unwell.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3. Other hazards

Cumulative effects may results following exposure *. May produce discomfort of the respiratory system *. Eye contact may produce serious damage &. May possibly affect fertility *. May possibly be harmful to the foetus / embryo *.

REACH – Art. 57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS issue date.

SECTION 3. Composition / information on ingredients

P330 Rinse mouth

3.1 Substances

See 'Composition on ingredients' in Section 3.2

3.2 Mixtures

1. CAS No 2. EC No 3. Index No 4. REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP] and amendments	SCL / M-Factor	Nanoform Particle Characteristics
1. 593-84-0 2. 209-812-1 3. 615-030-00-5 4. Not Available	25 - 50	<u>quanidine</u> <u>thiocyanate</u>	Acute Toxicity (Oral) - Category 4, Acute Toxicity (Dermal) – Category 4 Acute Toxicity (Inhalation) – Category 4 Hazardous to the Aquatic Environment Long-Term Hazard – Category 3 H302, H312, H332, H412 ²	Not Available	Not Available
1. Not Available 2. Not Available 3. Not Available 4. Not Available	5 - 10	<u>Non-ionic</u> detergent	Acute Toxicity (Oral) – Category 4 Skin Corrosion/Irritation – Category 2 Serious Eye Damage / Eye Irritation – Category 1 Hazardous to the Aquatic Environment Long-Term Hazard – Category 2 H315, H318, H411, EUH066	Not Available	Not Available
Legend:	2. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 3. Classification drawn from C&L * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties				

SECTION 4. First aid measures

4.1. Description of first aid mea	sures
Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear ► Wash skin and hair with running water (and soap if available) ► Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.

	▶ IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY
Ingestic	 For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed In the meantime, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of this SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of this SDS.
	 Where medical attention is not immediately available or where the patient is more than 15 minutes away from a hospital or unless instructed otherwise: INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. NOTE: wear a protective glove when inducing vomiting by mechanical means.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

For thiocyanate poisonings haemodialysis is recommended as the treatment of choice. Phenobarbital protects poisoned animals against death. Thiocyanate ion is slowly excreted in the urine and is not decomposed to any appreciable degree to cyanide. [GOSSELIN, SMITH & HODGE: Clinical Toxicology of Commercial Products 5th Ed]

SECTION 5. Firefighting measures

5.1 Extinguishing media

- Foam
- Dry chemical powder
- BCF (when regulations permit)
- Carbon dioxide
- Water spray or fog Large fires only

5.2 Special hazards arising from the substrate or mixture

Fire Incompatibility	• Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.
----------------------	---

5.3. Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO2) hydrogen chloride phosgene nitrogen oxides (NOx) sulfur oxides (SOx) other pyrolysis products typical of burning organic material. May emit corrosive fumes.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

See section 8

6.2 Environmental precautions

See section 12

6.3 Methods and material for containment and cleaning up

Minor Spills	 Environmental hazard – contain spillage Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Environmental hazard – contain spillage DO NOT touch the spill material Moderate hazard • Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • Wear breathing apparatus plus protective gloves • Prevent, by any means available, spillage from entering drains or water course. • Consider evacuation (or protect in place) • No smoking, naked lights or ignition sources. • Increase ventilation. • Stop leak if safe to do so. • Contain or absorb spill with sand, earth or vermiculite. • Collect recoverable product into labelled containers for recycling. • Collect solid residues and seal in labelled drums for disposal. • Wash area and prevent runoff into drains. • If contamination of drains or waterways occurs, advise emergency services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7. Handling and storage

7.1. Precautions for safe handling • Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. Prevent concentration in hollows and sumps. • DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. Safe handling ▶ Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions. ▶ DO NOT allow clothing wet with material to stay in contact with skin Fire and explosion protection See section 5 Store in original containers. ▶ Keep containers securely sealed. No smoking, naked lights or ignition sources. Other information ▶ Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
--------------------	--

Storage incompatibility	 Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. Metal cyanides are readily oxidised and those of some heavy metals show thermal instability. Metal cyanide and cyanates are often endothermic, Several members of this family of compounds, containing heavy metals tend to explosive instability, and most are capable of violent oxidation under certain circumstances. Fusion of mixtures of metal cyanides with metal chlorates, perchlorates, nitrates or nitrites cause violent explosion. Magnesium reacts with incandescence on heating with several metal cyanides; release of cyanogen by thermal decomposition may cause vigorous reaction with magnesium. Addition of one solid component (even in residual amounts) to another molten component is extremely dangerous. Nitriles may polymerise in the presence of metals and some metal compounds. They are incompatible with acids; mixing nitriles with strong oxidising acids can lead to extremely violent reactions. Nitriles are generally incompatible with other oxidising agents such as peroxides and epoxides. The combination of bases and nitriles can produce hydrogen cyanide. Nitriles are hydrolysed exothermally in both aqueous acid and base to give carboxylic acids (or salts of carboxylic acids). Nitriles can react vigorously with reducing agents. The covalent cyano group is endothermic and many organic nitriles are reactive under certain conditions; N-cyano derivatives are reactive or unstable. The majority of endothermic compounds are thermodynamically unstable and may decompose explosively under various circumstances of initiation. Many but not all endothermic compounds have been involved in decompositions, reactions and explosions and, in general significantly positive values of standard heats of formation, may be considered suspect on stability grounds.
Hazard categories in accordance with Regulation (EC) No 1272/2008	Not available
Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of	Not available

7.3. Specific end use(s)

See section 1.2

SECTION 8. Exposure controls / personal protection

8.1. Control	parameters
--------------	------------

Ingredient	DNELs Exposure Patte	ern Worker		PNECs Compartment	
	Dermal	0.31 mg/kg bw/day	(Systemic, Chronic)	42.4 mcg/L	(Water (Fresh))
	Inhalation	1.092 mg/m ³	(Systemic, Chronic)	4.24 mcg/L	(Water – Intermittent release)
	Inhalation	3.28 kg/m ³	(Systemic, Acute)	424 mcg/L	(Water (Marine))
guanidine thiocyanate	Dermal	0.155 mg/kg bw/day	(Systemic, Chronic) *	165 mcg/kg sediment dw	(Sediment (Fresh Water))
	Inhalation	0.27 mg/m ³	(Systemic, Chronic) *	16.5 mcg/kg sediment dw	(Sediment (Marine))
	Oral	0.155 mg/kg bw/day	(Systemic, Chronic) *	8.03 mcg/kg soil dw	(Soil)
				20 mg/L	(STP)

* Values for General Population

Occupational Exposure Limits (OEL)

INGREDIENT DATA Source Ingredient Material name TWA STEL Peak Notes Not Available Emergency Limits Ingredient TEEL-1 TEEL-2 TEEL-3 11 mg/m³ guanidine thiocyanate 0.98 mg/m³ 65 mg/m³

Ingredient	Original IDLH	Revised IDLH
guanidine thiocyanate	Not Available	Not Available

8.2. Exposure controls Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant. Type of contaminant Air Speed Solvent, vapours, degreasing etc. evaporating from tank (in still air) 0.25 - 0.5 m/s (50 - 100 f/min) Aerosols, fumes form pouring operations, intermittent container filling, low speed conveyer transfers, welding, 0.5 - 1 m/s (100 - 200 f/min) spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) Direct spray, spray painting in shallow boots, drum filling, conveyer loading, crusher debts, gas discharge 1 - 2.5 m/s (200 - 500 f/min) 8.2.1 Appropriate engineering (active generation into zone of rapid air motion) controls Grinding, abrasive blasting, tumbling, high speed generated dusts (released at high velocity into zone of very 2.5 - 10 m/s (500 - 200 f/min) high rapid air motion) Within each range the appropriate value depends to: Lower end of range Upper end of range 1: Room air currents minimal of favourable to capture 1: Disturbing room air currents 2: Contaminants of low toxicity or of nuisance value only 2: Contaminants of high toxicity 3: Intermittent, low production 3: High Production, heavy use 4: Small hood - local control only 4: Large hood or large air mass in motion Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. 8.2.2. Personal protection Chemical goggles. Safety glasses with side shields Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers Eve and face protection have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] Skin protection See Hand protection below Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of guality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact. chemical resistance of glove material, glove thickness and dexteritv Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 Hand / feet protection minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed mosturiser is recommended. See Other protection below Body protection Overalls. P.V.C apron. Other protection Barrier cream.Skin cleansing cream.

Eve wash unit.

Respiratory protection

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AB-AUS / Class1 P2	-
up to 50	1000	-	AB-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AB-2 P2
up to 100	10000	-	AB-3 P2
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

8.2.3. Environmental exposure controls

See section 12

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2. Other information

Not Available

SECTION 10. Stability and reactivity

10.1.Reactivity	See section 7.2	
10.2. Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 	
10.3. Possibility of hazardous reactions	See section 7.2	
10.4. Conditions to avoid	See section 7.2	
10.5. Incompatible materials	See section 7.2	
10.6. Hazardous decomposition products	See section 5.3	

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritatio Directives sing animal models). Nevertheless, adverse systemic effects have the and good hygiene practice requires that exposure be kept to a minimum and the Hydrogen chloride (HCI) vapour or fumes present a hazard from a single a humans in a few minutes. Inhalation of HCI may cause choking, coughing, burning sensation and mar followed by generalised lung damage may follow. Breathing of HCI vapour may aggravate asthma and inflammatory or fibroti High concentrations cause necrosis of the tracheal and bronchial epithelius pulmonary blood vessels and liver.	been produced following exposure of animals by at least on other route hat suitable control measures be used in an occupational setting. Icute exposure. Exposures of 1300 to 2000 ppm have been lethal to y cause ulceration of the nose, throat and larynx. Fluid on the lungs ic pulmonary disease.		
Ingestion	Accidental ingestion of the material may be harmful; animal experiments in produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastroi A number of materials such as cyanamide, calcium cyanamide, cyanates, cyanoacetates do not exhibit the same toxic effects as cyanides and nitrile. Probable lethal dose of thiocyanate (rhodanate), in man, is between 15 and with death coming in 10 to 48 hours.	intestinal tract following ingestion. isocyanates, isonitrile, thiocyanates, ferricyanide and ferrocyanide, and s.		
Skin Contact	There is some evidence to suggest that this material can cause inflammation of Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions to the use of the material and ensure that any external damage is suitably Skin contact with the material may be harmful; systemic effects may result f	s, may produce systemic injury with harmful effects. Examine the skin prior protected.		
Eye	If applied to the eyes, this material causes severe eye damage			
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the mucous membranes of the nose. Workers exposed to hydrochloric acid suffered from stomach inflammation and a number of cases of chronic bronchitis (airway inflammation) have also been reported. Repeated or prolonged exposure to dilute solutions of hydrogen chloride may cause skin inflammation.			
TR Wash	ΤΟΧΙCITY	IRRITATION		
i R Wash	Not Available	Not Available		
Guanidine thiocyanate	TOXICITY Dermal (rabbit) LD50: > 2000 mg/kg ^[2] Inhalation(Rat) LC50: > 0.853 mg/l4h ^[1] Oral (Rat) LD50: 474.6 mg/kg ^[2]	IRRITATION Skin: adverse effect observed (Corrosive) ¹		

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances



See Section 111

1.

2.

SECTION 12. Ecological information

	Endpoint	Test duration (hr)	Species	Value	Source
TR Wash	Not available	Not available	Not available	Not available	Not available
	Endpoint	Test duration (hr)	Species	Value	Source
	NOEC(ECx)	504	Crustacea	1.25 mg/l	2
Guanidine thiocyanate	EC50	72	Algae or other aquatic plants	130 mg/l	2
	EC50	96	Fish	42.4 mg/l	2
	LC50	48	Crustacea	~ 89.1 mg/l	2
Legend:	Extracted from	1. IUCLID Toxicity Data 2.	Europe ECHA Registered Substances - Ecotoxicol	ogical Information - Aquatic Toxic	ity 4. US EPA,
Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japa - Bioconcentration Data 8. Vendor Data			a 7. METI (Japan)		

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Thiocyanates:

Terrestrial Fate: Soil - At near ambient temperatures (approximately 30 C.) it appears that sorption and volatilization are not significant processes for thiocyanate in soil, with thiocyanate losses due primarily to microbial degradation. Thiocyanate is not persistent in soils. Thiocyanate may undergo both aerobic and anaerobic microbial degradation; however, the degradation pathway has not been defined. Saturated soils treated with thiocyanate were found to emit carbonyl sulfide (COS). Microbial degradation is the primary mechanism for thiocyanate disappearance at or below 30 C., with carbonyl sulfide as a possible hydrolysis product. Loss of thiocyanate at higher temperatures (50-60 C.) did not appear to result from microbial degradation.

Aquatic Fate: Biodegradation is a significant transformation process for thiocyanates in natural waters. Thiocyanate is toxic to microorganisms at high concentrations; however, acclimated cultures have increased tolerance to this compound. At concentrations up to 1.42 g/L., thiocyanate is completely degraded within 4 days to ammonia and sulfate ion (SO4-2) by an acclimatized co-culture of two bacteria (Acinetobacter johnsonii and Pseudomonas diminuta).

 $\ensuremath{\text{DO}}\xspace$ NOT discharge into sewer or waterways.

12.2. Persistence and degradability

No data available No data available	Ingredient	Persistence: Water/Soil	Persistence: Air
		No data available	No data available

12.3. Bio accumulative potential

Ingredient	Bioaccumulation
	No data available

12.4. Mobility in soil

Ingredient	Mobility
	No data available

12.5. Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT	×	×	×
vPvB	×	×	×
PBT Criteria fulfilled? No			
vPvB	No		

12.6. Endocrine Disruption Properties

Not Available

12.7. Other adverse effects

Not Available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

	Containers may still present a chemical hazard/ danger when empty.
	Return to supplier for reuse/ recycling if possible.
	Otherwise:
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
	Where possible retain label warnings and SDS and observe all notices pertaining to the product.
	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their
	area. In some areas, certain wastes must be tracked.
	A Hierarchy of Controls seems to be common - the user should investigate:
	▶ Reduction
	▶ Reuse
	► Recycling
	▶ Disposal (if all else fails)
Product / Packaging disposal	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be
	applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.
	DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	 In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.
	 Recycle wherever possible or consult manufacturer for recycling options.
	Consult State Land Waste Authority for disposal.
	 Bury or incinerate residue at an approved site.
	▶ Recycle containers if possible, or dispose of in an authorised landfill.
Vaste treatment options	Not Available
ewage disposal options	Not Available

SECTION 14 Transport information

Labels Required Marine Pollutant NO Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS 14.1. UN number Not Applicable 14.2. UN proper shipping Not Applicable name Class Not Applicable 14.3. Transport hazard class(es) Not Applicable Sub risk 14.4. Packing group Not Applicable 14.5. Environmental hazard Not Applicable Hazard identification (Kemler) Not Applicable Classification code Not Applicable Hazard Label Not Applicable 14.6. Special precautions for user Special provisions Not Applicable Limited quantity Not Applicable Tunnel Restriction Code Not Applicable

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable			
14.2. UN proper shipping name	Not Applicable	Not Applicable		
	ICAO/IATA Class	Not Applicable		
14.3. Transport hazard	ICAO / IATA Sub risk	Not Applicable		
class(es)	ERG Code	Not Applicable		
14.4. Packing group	Not Applicable			
14.5. Environmental hazard	Not Applicable			
	Special provisions		Not Applicable	
	Cargo Only Packing In	structions	Not Applicable	
	Cargo Only Maximum Qty / Pack		Not Applicable	
14.6. Special precautions for user	Passenger and Cargo	assenger and Cargo Packing Instructions		
user	Passenger and Cargo Maximum Qty / Pack		Not Applicable	
	Passenger and Cargo	Limited Quantity Packing Instructions	Not Applicable	
	Passenger and Cargo	Limited Maximum Qty / Pack	Not Applicable	

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. UN proper shipping name	Not Applicable		
14.3. Transport hazard	IMDG Class Not Applicable		
class(es)	IMDG Sub risk Not Applicable		
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
	EMS Number Not Applicable		
14.6. Special precautions for user	Special provisions Not Applicable		
	Limited Quantities Not Applicable		

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable	
14.2. UN proper shipping name	Not Applicable	
14.3. Transport hazard class(es)	Not applicable	Not Applicable
14.4. Packing group	Not applicable	
14.5. Environmental hazard	Not applicable	
	Classification code	Not Applicable
	Special provisions	Not Applicable
14.6 Special precautions for user	Limited quantity	Not Applicable
	Equipment required	Not Applicable
	Fire cones number	Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.8. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Guanidine thiocyanate	Not Available
Non-ionic detergent	Not Available

14.9. Transport in bulk in accordance with the ICG Code

Product name	Ship Type
Guanidine thiocyanate	Not Available
Non-ionic detergent	Not Available

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

guanidine thiocyanate is found on the following regulatory lists

Europe EC Inventory European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

Information according to 2012/18/EU (Seveso III):

Seveso Category Not Available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

ECHA SUMMARY

Ingredient	CAS number Index No		ECHA Dossier	
Guanidine thiocyanatee	593-84-0	615-004-00-3		Not Available
Harmonization (C&L Inventory)	Hazard Class and Category Code(s)		Pictograms Sigr Word Code(s)	nal Hazard Statement Code(s)
1	Acute Tox. 4; Acute Tox. 4; Acute Tox. 4; Aquat	tic Chronic 3;	GHS07; Wng	H302; H312; H332, H412
2	Acute Tox. 4; Skin Corr. 1B. Eye Dam 1; Aquatic Chronic 3 ; Acute Tox. 3; Acute Tox. 3; Aquatic Acute 3; STOT SE 3		GHS05; Dgr; GH GHS08	S06, H301; H312; H314; H318; H331; H335; H402; H412

Harmonization Code 1 = The most prevalent classification. Harmonization Code 2 = The most severe classification.

National Inventory Status

inational involutory otatao	
National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (guanidine thiocyanate; Non-ionic detergent)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (Non-ionic detergent)
Japan - ENCS	No (guanidine thiocyanate)
Korea - KECI	No (guanidine thiocyanate)
New Zealand - NZloC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes

Taiwan - TCSI	Yes
Mexico - INSQ	No (guanidine thiocyanate; Non-ionic detergent)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16. Other information

Full text Risk and Hazard codes

Toxic if swallowed
Harmful in contact with skin
Causes serious eye damage
Toxic if inhaled
Harmful if inhaled
May cause respiratory irritation.
Harmful to Aquatic life

Version Summary

Version	Date of Update	Sections Updated
1	30/APR/2024	Initial version

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered. For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
AIIC	Australian Inventory of Industrial Chemicals
BCF:	Bio Concentration Factors
BEI	Biological Exposure Index
DSL	Domestic Substances List
EINECS	European INventory of Existing Commercial chemical Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and New Chemical Substances Inventory
ES	Exposure Standard
FBEPH	Russian Register of Potentially Hazardous Chemical and Biological Substances
IARC	International Agency for Research on Cancer
IECSC	Inventory of Existing Chemical Substance in China
IDLH	Immediately Dangerous to Life or Health Concentrations
INSQ	Inventario Nacional de Sustancias Químicas
KECI:	Korea Existing Chemicals Inventory
LOAEL	Lowest Observed Adverse Effect Level
LOD	Limit Of Detection
NCI	National Chemical Inventory
NDSL	Non-Domestic Substances List
NLP	No-Longer Polymers
NOAEL	No Observed Adverse Effect Level
NZIoC:	New Zealand Inventory of Chemicals
OSF	Odour Safety Factor
OTV	Odour Threshold Value
PC	Permissible Concentration
PC-STEL	Permissible Concentration Short Term Exposure Limit
PICCS	Philippine Inventory of Chemicals and Chemical Substances
STEL	Short Term Exposure Limit
TCSI	Taiwan Chemical Substance Inventory
TEEL	Temporary Emergency Exposure Limit
TLV TSCA	Threshold Limit Value Toxic Substances Control Act
TWA	Time Weighted Average